

Rust Veto 210-C

Light oil rust preventative

DESCRIPTION

Rust Veto 210-C is a new addition to the Houghton line of oil type rust preventives that displaces and separates water. The product exhibits a light oily film, if applied properly, and offers up to one year of indoor rust protection.

FEATURES/ BENEFITS

- High flash- 260°F (126.7°C)
- Displaces water
- Separates water
- Excellent Humidity rust protection
- Easily removed
- Barium free
- Thin film protects your parts without excessive carry-off which reduces usage and cost.
- Low-odor nature of the products optimizes worker acceptance.
- Displaces water or process fluids from wet parts to rapidly begin the corrosion inhibition process.
- Separates any displaced water from itself to optimize both corrosion inhibition and bath life.
- The high flash point reduces the potential for flammability and may reduce fire insurance premiums.
- Rapid drying permits handling of parts shortly after application which expedites process flow and packaging.

DATA (TYPICAL VALUES)

Appearance	Clear, amber
Specific gravity	0.838
Viscosity at 100°F SUS (38°C)	40 SUS
Copper Corrosion	1a
ASTM D-130	
Flash Point, C.O.C.	260°F
Fire Point, C.O.C.	270°F
Film Thickness	0.26 mls
Film Type	Light, oily
Water Displacement	Passes
Water Separation	Passes
Humidity at 120°F/100% RH Polished Panels	Passes 30+ days

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date | version
Code



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.