

# PRODUCT DATA

## RUST VETO® 266

### FINGERPRINT SUPPRESSOR AND NEUTRALIZER

**Rust Veto 266** is a combination rust preventive - cleaner - fingerprint neutralizer and suppressor. It also possesses water displacing properties, forming a very thin film on the metal which removes water by preferential wetting of the metal surface. The attraction of the preservative for the metal surface is greater than that of water, consequently water is displaced.

### TYPICAL PHYSICAL AND PROTECTIVE PROPERTIES

Flash Point	100°F (37.7°C) minimum
Viscosity @ 100°F (40°C)	35 sec. (2.65 cSt)
Film Thickness (dip)	.0002"
Pour Point	-60°F (-51.1°C)
Humidity Cabinet @ 120°F (48.8°C)	14 days
Gravity @ 60°F (15.5°C)	35 PAI (0.84)
Type of Film	Thin, oily
Coverage	1200 sq. ft./gal. (39.5 m <sup>2</sup> /l)
Pounds per Gallon	7.05 (.846 kg/l)

### RECOMMENDED USES

Normally used for its fingerprint neutralizing qualities, **Rust Veto 266** also serves well as an intra-plant temporary preventive for the protection of parts from corrosion between operations. It offers an easy means for preserving parts which have been wetted out by contact with cutting, cooling, quenching or cleaning solutions.



**Houghton International Inc.**

Madison and Van Buren Ave., P. O. Box 930, Valley Forge, PA 19482-0930  
(610) 666-4000 Telefax (610) 666-1376

**RECOMMENDED USES (Con't.)**

**Rust Veto 266** may be used as a "special solvent" cleaner because of its water displacing property. This material removes perspiration residues and may be used following an organic solvent cleaning. It can also be used to neutralize acid contaminants which may remain on work after pickling or plating.

**EASILY APPLIED AND REMOVED**

**Rust Veto 266** may be applied by dip, spray, or brush up to 95°F. It can be removed readily using kerosene, petroleum solvent or Houghto-Clean 240 alkaline cleaner. Use at four to six ounces per gallon of water at 180-190°F. The oily film of **Rust Veto 266** should be completely removed before the proper Rust Veto is applied for permanent protection.

**SHIPPING INFORMATION**

**Rust Veto 266** is shipped in 55 (U.S.) gallon (208 liter) metal drums.

**SHIPPING CLASSIFICATION**

Combustible Liquid - NOS  
Petroleum Lubricating Oil - NOS

**STORAGE/HANDLING/DISPOSABILITY**

No health or safety hazards exist when **Rust Veto 266** is stored, used and disposed of in accordance with instructions given on the Material Safety Data Sheet for this product.

**WARRANTY**

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of Houghton products are not to be construed as recommending the infringement of any patent.

**EXPORT STATEMENT**

This commodity and its technology are subject to the export control laws and regulations of the United States Government. Buyer agrees that it shall not make any disposition, by way of export, diversion, transshipment, re-export or otherwise, except as expressly permitted under United States law.

**10/96**