

# PRODUCT DATA

## HI-TEMP® OILS 305 & 309

**Hi-Temp 300 Series Oils** are molybdenum disulphide containing oils intended for lubrication of bearings and conveyor chain at temperatures of 750°F or lower.

**Hi-Temp 300 Series Oils** have excellent bearing load capability needed to lubricate conveyor chain and trolley wheels.

<u>TYPICAL PHYSICAL PROPERTIES</u>	<u>HI-TEMP® 305</u>	<u>HI-TEMP® 309</u>
Viscosity, @ 104°F SUS	85	90
Flash Point, °F, COC	355	355
Fire Point, °F, COC	395	395
Pour Point, °F	0	0

### BENCH TEST

Shell-4-Ball Weld Point	190 kg	140 kg
-------------------------	--------	--------

### STORAGE/HANDLING/DISPOSABILITY

No health or safety hazards exist when **Hi-Temp 305** or **309** are stored, used and disposed of in accordance with instructions given on the Material Safety Data Sheet for this product.



**Houghton International Inc.**

Madison and Van Buren Ave., P. O. Box 930, Valley Forge, PA 19482-0930  
(610) 666-4000 Telefax (610) 666-1376

**WARRANTY**

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of Houghton products are not to be construed as recommending the infringement of any patent.

**EXPORT STATEMENT**

This commodity and its technology are subject to the export control laws and regulations of the United States Government. Buyer agrees that it shall not make any disposition, by way of export, diversion, transshipment, re-export or otherwise, except as expressly permitted under United States law.

9/00