

MATERIAL SAFETY DATA SHEET

XTREME CUT 250C

SECTION 1:
IDENTIFICATION

Company Name:	QUALICHEM, INC.
Address:	P.O. BOX 926 SALEM, VA 24153
Phone No.	(540) 375-6700
Fax No.	(540) 375-3880
Emergency Phone No.	CHEM-TEL 800-255-3924
Date Prepared:	4/18/02
Date Revised:	2/15/10

SECTION 2:
INGREDIENTS

<u>MATERIAL</u>	<u>CAS NO.</u>	<u>%</u>
DISTILLATES, PETROLEUM, HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	30-50
DIALKYLAMINE, FATTY ACID SALT	PROPRIETARY*	5-10

* The specific identity of this proprietary material will be made available to health professionals, employees, and designated representatives in accordance with the provisions outlined in 29CFR 1910.1200(i).

SECTION 3:
HEALTH HAZARDS

Ingestion:	MAY BE TOXIC BY INGESTION.
Inhalation:	NOT A LIKELY ROUTE OF EXPOSURE.
Skin Contact:	MAY BE AN IRRITANT
Eye Contact:	MAY CAUSE IRRITATION.
Other Information:	NONE KNOWN.

SECTION 4:
FIRST AID

Ingestion:	DRINK SEVERAL GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENTION.
Inhalation:	REMOVE VICTIM TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST
Skin Contact:	WASH WITH PLAIN WATER OR SOAP AND WATER.
Eye Contact:	IMMEDIATELY FLUSH WITH CLEAR WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION IF IRRITATION PERSISTS.
Notes to Physician:	NONE KNOWN. TREAT SYMPTOMS WITH SUPPORTIVE MEASURES.

SECTION 5:
FIRE AND EXPLOSION HAZARD DATA

Flash Point/Method:	>325° F (CC)
Upper/Lower Limit in Air:	N.A./N.A.
Extinguishing Media:	WATER OR ANY MEDIA SUITABLE FOR THE SURROUNDING FIRE.
Procedures:	FIREFIGHTERS SHOULD WEAR NORMAL PROTECTIVE EQUIPMENT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED IN CONFINED AREAS.
Unusual Hazards:	NONE
Combustion Products:	PRODUCT WILL BURN UNDER FIRE CONDITIONS. OXIDES OF CARBON AND NITROGEN MAY BE PRODUCED.

SECTION 6:
ACCIDENTAL RELEASE MEASURES

Personal Precautions:	WEAR PERSONAL PROTECTIVE EQUIPMENT AS SPECIFIED IN SECTION 8. SPILLED MATERIAL CAN BE VERY SLIPPERY.
Procedures for Clean-up:	SMALL SPILLS - ABSORB IN SAWDUST OR ANY AVAILABLE ABSORBANT, PLACE RESIDUE IN SUITABLE CONTAINER FOR DISPOSAL. LARGE SPILLS - DIKE OR OTHERWISE CONTAIN LIQUID. ABSORB IN SAWDUST OR ANY AVAILABLE ABSORBANT, PLACE RESIDUE IN A SEALED, LIQUID-PROOF CONTAINER FOR DISPOSAL. CLEAN CONTAMINATED SURFACES WITH WATER OR AQUEOUS

MATERIAL SAFETY DATA SHEET

XTREME CUT 250C

	CLEANING AGENTS. OBEY ALL FEDERAL, STATE OR LOCAL REGULATIONS.
--	--

SECTION 7: HANDLING AND STORAGE

Handling: Storage:	AVOID EYE AND SKIN CONTACT. DO NOT TAKE INTERNALLY. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. STORE IN A COOL, DRY PLACE. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.
---------------------------	--

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Precautionary Measures: Engineering Controls: Control Limits: Equipment for Personal Protection:	STANDARD INDUSTRIAL HANDLING PRECAUTIONS. WASH THOROUGHLY AFTER HANDLING CHEMICALS. USE WITH ADEQUATE VENTILATION TO KEEP EXPOSURES BELOW OCCUPATIONAL EXPOSURE LIMITS. DISTILLATES, PETROLEUM, HYDROTREATED HEAVY NAPHTHENIC: ACGIH – 10 mg/m3 (STEL 15 min., oil mist); 5 mg/m3 (TWA, 8 hr, oil mist). OSHA – 5 mg/m3 (TWA, 8 hr., oil mist). WEAR CHEMICAL SAFETY GLASSES OR GOGGLES, PROTECTIVE GLOVES (RUBBER, NEOPRENE, ETC., AND STANDARD PROTECTIVE CLOTHING WHEN HANDLING THE CONCENTRATE. EYEWASH STATION IN AREA OF USE.
---	--

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Odor: pH (neat) pH (5% emulsion): Specific Gravity: Density: Solubility in Water: Boiling Point: Percent Volatile: VOC (ASTM 2369-04): Vapor Pressure (mmHg): Vapor Density: Evaporation Rate:	AMBER LIQUID. TRACE HYDROCARBON 9-10 8.8-9.2 0.94-0.96 7.93 lbs/gal. COMPLETE >212°F <20% (PRIMARILY WATER AND AMINE) 10.4% (0.83 lbs/gal) N.D. N.D. BUT HEAVIER THAN AIR (water=1): <1
--	---

SECTION 10: STABILITY AND REACTIVITY

Stability: Conditions to Avoid: Hazardous Polymerization: Conditions to Avoid: Incompatibility: Hazardous Decomposition Products:	STABLE NONE STABLE NONE STRONG OXIDIZING AGENTS, ACIDS OR ALKALIES. OXIDES OF CARBON AND NITROGEN WILL BE PRODUCED BY COMBUSTION.
--	--

SECTION 11: TOXICOLOGICAL INFORMATION

Materials and Tests: Carcinogenicity: Sensitization: Mutagenicity: Teratogenicity:	NO TOXICITY STUDIES HAVE BEEN CONDUCTED ON THIS PRODUCT. NO COMPONENT OF THIS PRODUCT IS LISTED AS A CARCINOGEN BY IARC, NTP, OR ACGIH. NOT A SENSITIZER. NO COMPONENT OF THIS PRODUCT IS CLASSIFIED AS A MUTAGEN. NO COMPONENT OF THIS PRODUCT IS CLASSIFIED AS A TERATOGEN
--	--

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:	NO TOXICITY TESTING HAS BEEN PERFORMED ON THIS PRODUCT.
--------------	---

MATERIAL SAFETY DATA SHEET

XTREME CUT 250C

SECTION 13: DISPOSAL CONSIDERATIONS

General Considerations: Procedures:	THIS PRODUCT WOULD NOT BE CONSIDERED AS A HAZARDOUS WASTE. DISPOSAL BY USE PREFERRED. DISPOSE OF THIS PRODUCT FOLLOWING ALL FEDERAL, STATE, OR LOCAL REGULATIONS.
--	---

SECTION 14: TRANSPORT INFORMATION

Shipping Name:	NOT REGULATED.
----------------	----------------

SECTION 15: REGULATORY INFORMATION

<u>Regulation</u> CERCLA (40 CFR302.4):	<u>Material</u> NONE	<u>RQ</u>	<u>Max. %</u>
SARA 302 (Sect. 355, Appendix A):	<u>Material</u> NONE	<u>TPQ</u>	<u>Max. %</u>
SARA 311/312:	<u>Categories</u> IMMEDIATE HEALTH	<u>Hazards</u> EYE IRRITANT	
SARA 313 (40 CFR 372.45):	<u>Material</u> NONE		<u>Max. %</u>
CWA (40 CFR 401.15):	NONE		
RCRA (40 CFR 261): Notes:	NONE THIS PRODUCT NOT A HAZARDOUS WASTE PER RCRA REGULATIONS.		
OSHA (29 CFR 1910.1200):	ALL COMPONENTS LISTED UNDER THIS STANDARD ARE SHOWN IN SECTION 2 OF THIS MSDS.		
WHMIS (Canada):	CLASS D-2B: MATERIAL CAUSING OTHER TOXIC EFFECTS (TOXIC). THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATIONS AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CONTROLLED PRODUCTS REGULATIONS.		
Inventories:	ALL INGREDIENTS IN THIS PRODUCT ARE LISTED IN TSCA AND DSL (CANADA) INVENTORIES.		

SPECIAL STATE REGULATIONS

<u>STATE</u>	<u>INGREDIENT</u>	<u>REGULATORY DESIGNATION</u>

SECTION 16 OTHER INFORMATION

SUGGESTED HAZARD RATINGS

<u>NFPA*</u>	<u>HAZARD</u>	<u>HMIS*</u>
1	HEALTH (Blue)	1
1	FIRE (Red)	1
0	REACTIVITY (Yellow)	0
	PERSONAL PROTECTION	B
	SPECIAL HAZARDS	

MATERIAL SAFETY DATA SHEET

XTREME CUT 250C

*Notes: 0 = Insignificant; 1 = Slight; 2 = Moderate; 3 = High; 4 = Extreme

The data contained in this Material Safety Data Sheet has been prepared based upon an evaluation of the ingredients in the product, their concentration in the product and potential interactions. The information is offered in good faith and is believed to be accurate. It is furnished to the customer who is urged to study it carefully to become aware of hazards, if any, in the storage, handling, use and disposal of the product; and to insure his employees are properly informed and advised of all safety precautions required. The information is furnished for compliance with the "Occupational Safety and Health Act" of 1970, the "Hazards Communication Act" of 1983 as well as various other Federal, State and Local regulations. Use or dissemination of all or part of this information for any other purpose is prohibited by law.

Revision 16.3